

GXD8 Operational Manual

.....

Revision 1.0



CONTENTS

CONTENTS	I
IMPORTANT NOTES	1
Unpacking Power Location Mounting Positions Conformity Technical Support	1 1 1 1 1
LAYOUT OF THIS MANUAL	2
INTRODUCTION TO THE GXD8	3
Description	3 3
FRONT PANEL DESCRIPTION	4
Panel Buttons	4
AUDIO FORMATS	5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
Audio Mute	6 6 6
	(7
Lock Mode Precision	77777777777
METERS AND INPUT LEVEL	9
Peak Hold	9 9 9 9
BACK PANEL	D
SPECIFICATION11	1
D/A Performance	1 1

Important Notes

Unpacking

After unpacking the GXD8, save all the packing materials in case you ever need to ship the unit. Thoroughly inspect the GXD8 for signs of damage. Report any shipment damage to the carrier at once. The following accessories are included with the GXD8:-

- 1. Power Cable.
- 2. User Guide.
- 3. Four mounting feet and screws.
- 4. Four rack mounting bolts.

Power

- This unit is equipped with voltage-selectable linear power supply. Please ensure that the correct voltage for you region is selected (110V or 220V) before plugging into the supply.
- Make sure that the unit is turned off before connecting the power plug to the socket.
- Please be sure to connect the power cord to the AC inlet on this unit before connecting the power plug to the socket.
- When disconnecting the power plug from the socket, do not pull the cord but hold the plug to avoid damaging the cord.
- Avoid damaging the power cord.
- If the unit is not to be used for a long period of time, unplug the cord from the socket.
- It is normal for this unit to become warm whilst being operated.

Location

- Avoid using this device in extreme heat, humidity or where it may be affected by dust or vibration.
- Do not place or drop anything heavy on the unit or its power cable.
- Ensure that the GXD8 has adequate ventilation space on all sides. We recommend at least 1U rack space top and bottom.

Mounting Positions

Do not mount the GXD8 upside down.

Conformity

The GXD8 bears the 'CE' mark and is therefore fully compliant.

Technical Support

Technical Support is available on line through the Genex web site at: <u>http://www.genex.co.uk/</u> or by emailing: <u>support@genex.co.uk.</u>

Layout of this Manual

Sections in this manual appear in the following order.

- 1. A brief introduction to the feature set and a list of options.
- 2. A detailed front panel description with a functional description of every front panel button and display. This section should be used as a quick guide and reminder to basic front panel operations.
- 3. A description of the audio formats supported
- 4. An explanation of the clock structure
- 5. Rear panel schematics and connector details

Introduction to the GXD8

Description

The GXD8 is a professional, 8-channel, digital to analogue audio converter, supporting all standard sample rates from 44.1kHz up to 192kHz up to 24 bits. It also supports the Sony DSD format (1-bit, 2.8224MHz sample rate $\Delta\Sigma$) when married with the DSD upgrade kit (available separately).

All settings are available from the intuitive front panel with no complex menu structures to navigate. The front panel also includes 8 high resolution peak power meters (PPMs), one for each channel.

As standard, the GXD8 is fitted with four AES/EBU digital inputs providing eight channels of analogue audio output up to 96kHz and four channels of output for 192kHz (an additional four channels are available via the AES expansion card). In addition, expansion card with ADAT, TDIF, SDIF and workstation interfaces on are available.

Options

- 8-channel DSD upgrade kit. Includes the input and processor card
- 8-channel AES expansion input and output card
- ADAT input / output card
- TDIF input / output card
- 8-channel SDIF2 input card
- Workstation input / output card

Front Panel Description

Panel Buttons

1. Mute

Mutes the digital audio output from the unit

2. Over Sensitivity

This button determines how many consecutive maximum value sample will trigger the "OVER" LED to light

3. Peak Delay

Sets the peak hold of the PPMs to either on, delay (2 seconds) or off

4. Fine PPM

Changes the PPM mode to a scale of ± 1 dB centred around -12, -14, -16, -18 and -20dBFS to aid input level calibration

5. Clear Peak Hold

Clears any peak or over LEDs on the PPMs that are lit

6. Configuration

Selects between the following input sources: AES, slot one (digital) and slot two (digital). In addition, for AES input the output format can be set to either PCM or DSD via the decoded bitsplit format

7. Lock Mode

Selects between the "wide" and "precision" lock modes when the unit is locked to an external clock source.

8. Clock Source

Selects the clock source for the unit – master (internal precision-cut quartz crystal), external word clock, slot one or slot two

9. AES Input

Chooses between single, dual or quadwire. Obviously, not all modes are available for all sample rates

10. Bit Split

Selects if to decode a PAQRAT bitsplitting format (PCM mode) or a 4-wire "DSD over AES" format.

11. Bit Depth

Displays resolution of input audio

12. Sample Rate

Allows selection of 44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz and 192kHz. This button does not function in DSD mode (forced to 44.1kHz) or in slave clock mode (locks automatically to input rate)

13. PPM DISPLAY

The PPM displays consists of eight columns of 14 segments each, representing channels 1 to 8 respectively. The meters are digital and are calibrated in dBFS, with the top segment representing 0dBFS. Peak values can be set to decay immediately, be held for 2 seconds before decaying, or can be held until the CLEAR PEAK HOLD button is pressed.

Note the overload segments remain on until cleared by the pressing the CLEAR PEAK HOLD button.

Audio

Audio Formats

This section describes how to configure the audio output section of the GXD8. The following parameters can be adjusted;

Standard Input Format

AES.

Input/Output Formats Available Through Expansion Cards

AES (expansion card to provide 8 channel dual wire 192kHz output)

SDIF-2 output

SDIF-2 input

TDIF

ADAT

DSD (Direct Stream Digital) - input only

What is Direct Stream Digital?

DSD was invented and developed by the Sony Corporation. It is designed to remove some of the potential artifacts introduced by the decimation filter in a conventional analogue to PCM digital conversion process. The DSD modulator generates a 2.8224MHz bitstream per channel, which is a slightly larger bandwidth than for 24 bit 96kHz PCM audio.

AES Input Configuration

You can select single wire, dual wire or quad wire. The setting refers to the position of consecutive samples within an audio carrier.

In single wire mode each consecutive audio sample for a given track is located within that track. For the AES format this means that one AES cable can carry two tracks of information.

Dual wire mode means that each consecutive audio sample is contained in adjacent tracks. For the AES format this means that one AES cable can carry only one track of information.

Quad wire mode means that successive audio samples rotate through four adjacent tracks. For the AES format this means that two AES cables carry one track of information.

In master clock mode:-

- at 44.1kHz or 48kHz sample-rate, the AES output is single wire and the button is disabled.
- at 88.2kHz or 96kHz sample-rate, the AES output can be either single or dual wire.
- at 176.4kHz or 192kHz sample-rate, the AES output can be either dual or quad wire.

In slave clock mode:

- with an input clock of 44.1kHz or 48kHz, the AES output can be single, dual or quad
- with an input clock of 88.2kHz or 96kHz, the AES output can be single or dual

Input configuration available		SAMPLE RATE						
		44.1kHz	48kHz	88.2kHz	96kHz	176.4kHz	192kHz	
NUMBER OF TRACKS	1-2 Tracks	Single	Single	Single Dual	Single Dual	Dual Quad	Dual Quad	
	3-4 Tracks	Single	Single	Single Dual	Single Dual	Dual Quad*	Dual Quad*	
	5-6 Tracks	Single	Single	Single Dual*	Single Dual*	Dual*	Dual*	
	7-8 Tracks	Single	Single	Single Dual*	Single Dual*	Dual*	Dual*	

* - only available with the AES, TDIF, ADAT or SDIF expansion card in slot 2

Bit Split Decode

Two different bit-split formats are used depending on whether the GXD8 is in PCM or DSD mode.

PCM mode. The Paqrat[®] format is supported. This allows 24-bit recordings to be made in legacy 16-bit recorders. Two channels on the recorder are required per 24-bit audio channel. The left channel contains the first 16-bits and may be monitored. The right channel contains the top eight bits plus a rather unpleasant tone (750Hz at 48kHz; 689Hz at 44.1kHz) at -19dBFS. The tone provides signal present confirmation for the level meters on the recorder but should not be monitored through any speakers.

DSD mode. Decodes to stereo on outputs one and two a DSD bitstream bit-mapped across eight 16-bit PCM channels (i.e., 4 AES cables). This allows stereo DSD recordings to be made on legacy 8-channel 16-bit PCM machines. Tape based recorders may still not be suitable however as the error correction techniques that have to be employed for digital tape will further corrupt the DSD stream over and above any errors on the tape in the first place!

Audio Mute

The mute button mutes the audio at the outputs only, right at the converters The PPMs will still display the input level.

Single-ended Output

It is possible to connect the balanced output of the GXD8 to a single-ended input. However, as the output is electronically balanced, the following precautions should be followed or the audio will be very distorted and noisy:

- Connect Pin 2 (signal) of the XLR to the target input
- Connect Pin 1 (ground) of the XLR to the target ground
- DO NOT connect the negative signal of the XLR output (pin 3), to ground (pin 1). Instead, leave the pin unconnected.

Clocks

It is vitally important that the clock used at the point of conversion between the analogue and digital domains is stable and accurate. Ideally the GXD8 should be the clock master wherever possible, as the unit uses a very stable fixed crystal oscillator to generate it's own clocks. However, operating with the GXD8 in master mode is not always possible, so the unit provides several methods for locking to external sources where necessary.

Lock Mode

Precision

The precision locking mode should always be selected in the first instance. The precision mode uses a very heavily damped phase locked loop that is designed to severely attenuate any clock jitter present on the input source. The downside is, that if the input clock varies or drifts too much in frequency, then lock will not be possible.

Wide

Wide mode should be used when the precision mode is not capable of locking to the external source. A more relaxed phase locked loop is selected in this mode, with less attenuation of jitter.

Clock Source

The clock source can be either Master, external word-clock, slot one or slot two.

Master

This selects the precision quartz crystal oscillator. This is the preferred lock source. The audio converter should always be the clock master wherever possible.

AES

Selects the AES inputs as the clock source. The unit will lock to the first AES input that is connected (i.e., if AES input 1/2 is not connected it will lock to AES 3/4 and so on).

External Word Clock

This selects the word clock input BNC at the back of the unit. The frequency should be x1 sample rate for single wire, $\frac{1}{2}$ sample rate for dual-wire and $\frac{1}{4}$ sample rate for quad-wire.

Slot One

This selects the card in slot 1 as the clock source.

Slot Two

This selects the card in slot 2 as the clock source.

Note that the DSD and SDIF cards cannot provide a clock source.

Sample Rate

The GXD8 supports the following PCM sample rates:-

44.1kHz; 48kHz; 88.2kHz; 96kHz; 176kHz; 192kHz

In addition, when locked to an external clock, the GXD8 supports all modified rates based around 44.1kHz and 48kHz (\pm 0.1%, \pm 4%). The GXD8 may also lock to 32kHz, although this is not guaranteed. Input **clock** rates from to 50kHz, plus 88.2kHz and 96kHz may be applied.

When the GXD8 is in MASTER clock mode, the sample-rate is selected pressing the sample rate button until the desired rate is indicated.

When locked to an external clock source, the incoming clock rate will be calculated and indicated. The LED will flash until the unit has obtained lock. If the incoming rate is a "modified" rate, then the up or

down arrow will also light to indicate a pull-up or pull-down rate respectively (see note below). The sample rate button is disabled in this case. However, single, dual or quad-wire mode can now be selected. The indicated rate will change based on the output wire configuration. For example:-

- A clock rate of 48kHz is connected to the clock input and detected:
 - In single-wire mode, a sample-rate of 48kHz will be indicated In dual-wire mode, a sample-rate of 96kHz will be indicated In guad-wire mode, a sample-rate of 192kHz will be indicated

In this way, the GXD8 always displays the actual **sample** rate rather than the external **clock** rate. Note that when locked to a clock rate of 88.2kHz or 96kHz only single or dual-wire mode may be selected.

NOTE: When either of the pull-up / pull-down LEDs are lit, the GXD8 is using a fast reacting, wide locking RC Phase Locked Loop instead of its variable crystal oscillators. As a result, the GXD8 may not notice if you subsequently change the incoming sample rate, particularly if you change from a $\pm 0.1\%$ modified to the unmodified rate. In this case, to ensure the GXD8 locks to the new unmodified rate using its variable crystal oscillator (which has far greater jitter performance and thereby greater audio conversion quality), the unit should be forced to relock (just cycle the unit through to master clock mode and back again).

Meters and Input Level

Eight high resolution peak power meters (PPMs), one for each channel, are provided. Four buttons are provided to configure the meters.

Peak Hold

The meters default to peak hold **on** on power-up. The peak value of any signal will be held until the **CLEAR PEAK HOLD** button is pressed.

With peak hold **delay**, each peak value is held for approximately 2 seconds or until the **CLEAR PEAK HOLD** button is pressed.

With peak hold set to off (both indicators off) no peak values will be held.

The **over** LEDs will always light when an over condition is detected. Setting peak hold to off or delay has no effect. They can only be cleared down by pressing **CLEAR PEAK HOLD**.

Fine PPM

This function changes the resolution and display style of the PPMs. The range of the PPMs changes to ± 1 dB centred around -12dBFS, -14dBFS, -16dBFS, -18dBFS or -20dBFS.

Over Sensitivity

This allows the number of adjacent "over" samples that are must be detected before the **OVER** LEDs are lit to be set from between one to six.

Output Gain Level

Below each PPM is a trim position to set up the input level for each channel. The output gain range is from -10dBu to +4dBu (for a -18dBFS input level). Therefore for full-scale (0dBFS) the GXD8 can output from +8dBu to +22dBu.

Back Panel

The back panel contains:-

- Eight balanced analogue outputs on XLR connectors
- Four balanced AES-EBU inputs on XLR connectors
- One word-clock input on 75Ω BNC. This should be externally terminated
- One work-clock output on 75Ω BNC
- Two slot interfaces. The top slot is Slot One. These accept a range of Genex options cards
- One AC mains input on an IEC connector. Mains supply must be 100-120V or 200-240V, 50/60Hz. The correct voltage range must be selected via the voltage selection switch above the IEC mains input. Failure to do so may result in severe damage to the unit.

Specification

D/A Performance

Resolution	upto 24 Bits
Signal / Noise ratio (un-weighted)	better than 113dB @ 20kHz bandwidth
THD + Noise ratio	better than -96dB @ -1dBFS, 1kHz
Frequency Response (±0.5dB)	5Hz to 22kHz @ 48kHz Fs
	5Hz to 44kHz at 96kHz Fs
	5Hz to 80kHz at 192kHz Fs
Miscellaneous	

Power r	requirements	100-120V, 200-240	OV. 50/60Hz (switched)

